



# SAFETY DATA SHEET

SDS REVISION DATE: January 21, 2021

Product ID: GMS1301A, GMS1316A

GMS Industrial Supply, Inc.  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • [www.GreenOger.com](http://www.GreenOger.com)

0024

24-Hour Emergency Telephone: 1-800-424-9300 CHEMTREC

## SECTION I - IDENTIFICATION

**PRODUCT IDENTIFIER:** Slick Ride  
**PRODUCT NUMBER:** GMS1301A, GMS1316A  
**RECOMMENDED USE:** Dry Silicone Spray  
**RESTRICTIONS ON USE:** None Known  
**COMPANY NAME:** GMS Industrial Supply, Inc.  
**COMPANY ADDRESS:** 212 Denn Lane, Virginia Beach, VA 23462  
**COMPANY PHONE:** (757) 473-1467  
**EMERGENCY PHONE:** CHEMTREC 1-800-424-9300

## SECTION II – HAZARDS IDENTIFICATION


**CLASSIFICATION:** Flammable Aerosol: Category 1  
Liquefied Gas  
Skin Irritant: Category 2  
Specific Target Organ Toxicity (Repeated Exposure): Category 2  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Reproductive Toxicity: Category 2  
Aspiration Hazard: Category 1  
Eye Irritant: Category 2A

**HAZARD STATEMENT(S): DANGER:** Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor and/or get medical advice/attention if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

### SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Hexane	110-54-3	20-40%
Propane	74-98-6	10-30%
Butane	106-97-8	10-30%
Naphtha (petroleum), hydrotreated light	64742-49-0	10-30%
Silicone	63148-62-9	3-7%

### SECTION IV - FIRST AID MEASURES

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION:** If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

**INHALATION:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

**SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: drowsiness and dizziness

Oral: abdominal irritation, nausea, vomiting, and diarrhea

**CHRONIC HEALTH HAZARDS:** None known

**NOTE TO PHYSICIAN:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

### SECTION V – FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** CO<sub>2</sub>, Dry Chemical

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon

### SECTION VI – ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Eliminate all sources of ignition. absorb liquid with non-combustible material like vermiculite, sand or earth and clean up with mop or rag.

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION VII – HANDLING AND STORAGE

**HANDLING AND STORAGE:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

### SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Hexane	500 ppm	400 ppm
Propane	1000 ppm	1000 ppm
Butane	1000 ppm	1000 ppm
Naphtha (petroleum), hydrotreated light	500 ppm	Not Established
Silicone	Not Established	Not Established

**ENGINEERING CONTROLS / VENTILATION:** Use only outdoors or in a well-ventilated area.

**RESPIRATORY PROTECTION:** Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (section VIII) are exceeded.



**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Clear, Colorless Spray

**ODOR:** Solvent odor

**ODOR THRESHOLD:** N/D

**pH:** N/A

**MELTING POINT/FREEZING POINT:** N/D

**INITIAL BOILING POINT AND BOILING RANGE:** N/D

**FLASH POINT:** N/D

**EVAPORATION RATE:** >3 Fast

**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**EXPLOSIVE LIMIT LOWER (%):** N/D

**EXPLOSIVE LIMIT UPPER (%):** N/D

**VAPOR PRESSURE (mm Hg):** N/D

**VAPOR DENSITY (AIR=1):** N/D

**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.68 - 0.75

**SOLUBILITY(IES):** 0%

**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D

**AUTOIGNITION TEMPERATURE:** N/D

**DECOMPOSITION TEMPERATURE:** N/D

**VISCOSITY:** N/D

## SECTION X – STABILITY AND REACTIVITY

**REACTIVITY:** Certain plastics, rubber, strong oxidizers

**CHEMICAL STABILITY:** Stable

**POSSIBLE HAZARDOUS REACTIONS:** None Known

**CONDITIONS TO AVOID:** Temperatures greater than 122°F and sources of ignition.

**INCOMPATIBLE MATERIALS:** Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

**HAZARDOUS DECOMPOSITION PRODUCTS:** Silicone Dioxide, Carbon oxides, Formaldehyde

## SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** Heptane (142-82-5) LC<sub>50</sub> (Vapors, Mice) 1600 ppm

**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin

**EYES:** Causes irritation, redness, tearing, pain, blurred vision.

**INGESTION:** Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.

**INHALATION:** Causes dizziness, excessive or prolonged exposure may cause unconsciousness.

**SKIN:** Causes localized defatting, irritation, dermatitis.

**MEDICAL CONDITION AGGRAVATED:** Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: drowsiness and dizziness

Oral: abdominal irritation, nausea, vomiting, and diarrhea

**CHRONIC HEALTH HAZARDS:** None known

**CARCINOGENICITY:** OSHA: No ACGIH: N/A NTP: No IARC: N/A OTHER: CA Prop 65

## SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Not Established

**PERSISTENCE AND DEGRADABILITY:** Component or components of this product are not biodegradable.

**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.

**MOBILITY IN SOIL:** This product is mobile in soil.

**OTHER ADVERSE EFFECTS:** This material is toxic to aquatic life.

### SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

#### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, flammable

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

#### SHIPPING BY WATER:

##### VESSEL (IMO/IMDG)

**PROPER SHIPPING NAME:** Aerosols

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant

### SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Hexane (110-54-3) Reportable Quantity = 5,000 lbs

**SARA 311/312 HAZARD CATEGORIES:** Acute Health, Fire

**SARA 313 REPORTABLE INGREDIENTS:** None

**STATE REGULATIONS: CA Prop 65:** This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**INTERNATIONAL REGULATIONS:** All components are listed or exempted.

**NFPA HEALTH:** 1

**NFPA FLAMMABILITY:** 3

**NFPA REACTIVITY:** 0

**NFPA OTHER:** None

**HMIS HEALTH:** 1

**HMIS FLAMMABILITY:** 3

**HMIS REACTIVITY:** 0

**HMIS PROTECTION:** B

### SECTION XVI - OTHER INFORMATION

N/A = Not Applicable; N/D = Not Determined

Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Revision Date: January 21, 2021