



SAFETY DATA SHEET

SDS REVISION DATE: November 8, 2018

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA. 23462
(855) GRN-OGER

Product ID: GMS1502A

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

0018

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION


Product ID:	GMS1502A		
Product Name:	Seal It! Black		
Revision Date:	Nov 08, 2018	Date Printed:	Nov 08, 2018
Version:	3.0	Supersedes Date:	Sep 20, 2018
Manufacturer's Name:	GMS Industrial Supply, Inc.		
Address:	212 Denn Lane, Virginia Beach, VA. 23462		
Emergency Phone:	Chemtrec: 1-800-424-9300		
Information Phone Number:	757-473-1467		
Fax:	757-337-3734		
Product/Recommended Uses:	RTV Silicone Gasket Maker - Acetoxy		

SECTION 2) HAZARDS IDENTIFICATION

Classification

Eye Irritation - Category 2A
Gases Under Pressure Liquefied Gas
Skin Irritation - Category 2

Pictograms



Signal Word

Warning

Hazardous Statements - Physical

H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health

H319 - Causes serious eye irritation
H315 - Causes skin irritation

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves and eye protection.

Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

Precautionary Statements - Storage

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

Precautionary Statements - Disposal

No precautionary statement available.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0070131-67-8	METHYL SILOXANE LINEAR/CYCLIC	52% - 82%
0007631-86-9	SILICA, AMORPHOUS	5% - 12%
0064742-46-7	MINERAL SEAL OIL	1% - 4%
0004253-34-3	METHYLTRIACTOXYLSILANE	1% - 4%
0017689-77-9	ETHYLTRIACTOXYLSILANE	1% - 4%
0000075-37-6	DIFLUOROETHANE	1% - 2%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

No ill effects expected.

If exposed/feel unwell/concerned: Get medical attention.

Eye Contact

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

Skin Contact

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing media suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards in Case of Fire

Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

Fire-Fighting Procedures

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

Special Protective Actions

Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Ventilate the area. Wear appropriate protective clothing and equipment.

Recommended Equipment

Wear appropriate protective equipment (see Section 8).

Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 7) HANDLING AND STORAGE

General

Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Do not puncture or incinerate (burn) cans. Do not spray in eyes. Do not take internally.

Ventilation Requirements

Use in a well-ventilated place.

Storage Room Requirements

Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory Protection

In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
DIFLUOROETHANE		2.5			1							
MINERAL SEAL OIL	500	2000			1							
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2			1,3				6			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
DIFLUOROETHANE		2.5		
MINERAL SEAL OIL				
SILICA, AMORPHOUS				

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	1.81942 lb/gal
Density VOC	0.25160 lb/gal
% VOC	3.07800%
Appearance	Thick liquid under pressure (Viscous paste)
Odor Threshold	N.A.
Odor Description	Acetic Acid Odor
pH	N.A.
Water Solubility	N.A.
Flammability	Flash point at or above 200°F/93°C
Flash Point Symbol	N.A.
Flash Point	>100 °C(>212°F) Closed Cup (Liquid component)
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Density	N.A.
Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

Keep away from heat, sparks, extreme temperature, flame, other sources of ignition and incompatible materials.

Incompatible Materials

Strong acids, strong bases, strong oxidizing agents.

Hazardous Reactions/Polymerization

None known.

Hazardous Decomposition Products

Burning may produce silicon oxides; carbon oxides.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes skin irritation

Classification of the substance or mixture

There is no toxicological data available for this product.

Serious Eye Damage/Irritation

Causes serious eye irritation

Carcinogenicity

No data available

Germ Cell Mutagenicity

No data available

Reproductive Toxicity

No data available

Respiratory/Skin Sensitization

No data available

Specific Target Organ Toxicity - Single Exposure

No data available

Specific Target Organ Toxicity - Repeated Exposure

No data available

Aspiration Hazard

No data available

Acute Toxicity

No data available

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available

Classification of the substance or mixture

There is no ecological data available for this product.

Persistence and Degradability

No data available.

Bio-Accumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

UN number: UN1950

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.2

Packaging group: No Data Available

Hazardous substance (RQ): No Data Available

Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: No Data Available

IMDG Information

UN number: UN1950

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.2

Packaging group: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: No Data Available

IATA Information

UN number: UN1950

Hazard class: 2.2

Packaging group: No Data Available

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (N/A)

Note / Special Provision: No Data Available

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0070131-67-8	METHYL SILOXANE LINEAR/CYCLIC	52% - 92%	SARA312,TSCA
0007631-86-9	SILICA, AMORPHOUS	5% - 12%	SARA312,TSCA,OSHA
0064742-46-7	MINERAL SEAL OIL	1% - 4%	SARA312,TSCA,OSHA
0004253-34-3	METHYLTRIACETOXSIL ANE	1% - 4%	SARA312,TSCA
0017689-77-9	ETHYLTRIACETOXSILA NE	1% - 4%	SARA312,TSCA
0000075-37-6	DIFLUOROETHANE	1% - 2%	SARA312,VOC_exempt,TSCA,ACGIH,OSHA

SECTION 16) OTHER INFORMATION

Glossary


* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 1
FLAMMABILITY	1
Physical Hazard	0
Personal Protection	B

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Revision Date: November 8, 2018